

SHURFLO® WATER PRESSURE REDUCER VALVES (WPRV)

Shurflo Water Pressure Reducer Valves (WPRV) are fixed pressure, water-reducing devices (non-adjustable). The WPRV minimizes incoming water pressure fluctuations while guarding against pressure spikes. Actual pressure reduction is dependent upon input pressure and outlet flow rate.



PART NO	DESCRIPTION	PACK SIZE	LIST PRICE
A 183-130-SS	30 PSI [2.1 bar], inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings	30	\$48.20
A 183-150-SS	50 PSI [3.4 bar], inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings	30	48.20
A 183-165-SS	65 PSI [4.5 bar], inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings	30	48.20
A 183-180-SS	80 PSI [5.5 bar], inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings	30	48.20
B 183-150-PG	50 PSI [3.4 bar], inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings, stainless steel body and pressure gauge with follower	6	108.00
B 183-165-02	65 PSI [4.5 bar], inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings, stainless steel body and pressure gauge with follower	6	108.00
B 183-180-02	80 PSI [5.5 bar], inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings, stainless steel body and pressure gauge with follower	6	108.00
C 183-150-01	50 PSI [3.4 bar], inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings, stainless steel body	30	70.70
C 183-165-01	65 PSI [4.5 bar], inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings, stainless steel body	30	70.70
C 183-180-01	80 PSI [5.5 bar], inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings, stainless steel body	30	70.70
D 183-130-NF	1/2" NST, 30 PSI [2.1 bar], w/o fittings	12	44.40
D 183-150-NF	1/2" NST, 50 PSI [3.4 bar], w/o fittings	12	44.40
D 183-165-NF	1/2" NST, 65 PSI [4.5 bar], w/o fittings	12	44.40
E 183-165-QC14	65 PSI [4.5 bar], 1/4" [6.4 mm], John Guest® [JG] Fittings	12	45.50
E 183-165-QC38	65 PSI [4.5 bar], 3/8" [10 mm], JG Fittings	12	45.50
F EV3135-26	Pair of 1/2" [12.7 mm] and 1/4" [6.4 mm], JG Fittings	12	28.30
F EV3135-27	Pair of 1/2" [12.7 mm] and 3/8" [10 mm], JG Fittings	12	28.30

SHURFLO SOLD OUT SWITCHES (SOS)

Shurflo Sold Out Switches (SOS) prevent the dispensing of carbonated water without syrup by stopping water flow at the dispenser valve – a particularly useful feature for clear sodas. The SOS senses the pressure drop in the syrup line caused by an empty Bag-in-Box (BIB) and shuts off power to the valve's electric solenoid. The SOS automatically resets with the installation of a full BIB.



A



B

PART NO	DESCRIPTION	PACK SIZE	LIST PRICE
A 94-068-NF	8-30 PSI [0.55-2.10 bar] adjustment range, no fitting, 48" [122 cm] wiring cables and LED "sold-out" light – 24 VAC.	50	\$70.30
A 94-068-01	8-30 PSI [0.55-2.10 bar] adjustment range, 1/4" [6 mm] stainless steel tee barb, 48" [122 cm] wiring cables and LED "sold-out" light – 24 VAC.	50	117.00
A 94-068-20	8-30 PSI [0.55-2.10 bar] adjustment range, 3/8" [10 mm] stainless steel tee barb, extra long 78" [198 cm] wiring cables and LED "sold-out" light – 24 VAC.	50	201.00
B 94-068-31	Mini-Micro, 15-20 PSI [1.0-1.4 bar] adjustment range, 1/4" [6 mm] stainless steel tee barb, 48" [122 cm] wiring cables and LED light – 24 VAC.	N/A	201.00
B 94-068-33	Mini-Micro, 25-60 PSI [1.7-4.1 bar] adjustment range, 1/4" [6 mm] stainless steel tee barb, 48" [122 cm] wiring cables.	10	115.00